

## Technical Data Sheet

Printing date 01.06.2009  
page 1/1

# SOLTECH<sup>®</sup> *Premium* ACYRLIC MATT WHITE PAINT 315-1020

---

<b>Product Description</b>	: Acrylic resin based, isocyanate-cured, high hiding powered, elastic and hard, non-fading finishing white paint.
<b>Suggested Uses</b>	: Can be used in all interior furnitures, whose surface is prepared with Soltech Plus or Premium Polyurethane primer. Can also be used in metal surfaces, whose surface is prepared with Epoxy based primers.
<b>Application Equipments</b>	: Compatible with Airless and Airmix spray systems.
<b>Color, Appearance</b>	: White, viscous
<b>Solids Content (%)</b>	: 65 ± 2
<b>Density (g/ml)</b>	: 1,30 g/ml
<b>Gloss</b>	: 12 gloss at 60°
<b>Viscosity</b>	: DIN 6 (at 20 C°) 50 sec.
<b>Mixture Content</b>	: Varnish : 100 Hardener : 50 Thinner : 30
<b>Pot-life</b>	: 4 hours at 25 C°
<b>Dry Time</b>	: To Touch : 45 min. (at 25 C°), To Dry Hard : 12 hours (at 25 C°)
<b>Thinner</b>	: Soltech cellulosic, polyurethane or acrylic thinners.
<b>Storage Conditions</b>	: Recommended to be stored in cool and and dry places with proper ventilation and no direct sunlight exposure. Should be kept away from sources of fire and heat and necessary fire extinguishing measures should be taken.
<b>Consumption</b>	: 100 – 120 g/m <sup>2</sup>
<b>Flash Point</b>	: +4 C°
<b>Package Type</b>	: 10 kg

---

**Technical Consultancy, Application and Process:** Verbal, written or practical solutions and recommendations given by our technical service regarding the use of the products are based on the experience and knowledge of our company and does not remove the testing responsibility of the user regarding his/her intended use and is not binding in a way to include the rights of the related third persons. Application, usage and process of the products happen outside of our control opportunity and the entire responsibility belongs to the user. While the responsibility of our company is not fully eliminated, it is limited with the value measure of the products provided by us and consumed by the user. Needless to say, we guarantee the product continuance of all our products pursuant to our general sales and delivery conditions. New versions of this brochure override the previous ones. Please conform to EC safety forms.