

Technical Data Sheet



500-0050

Printing date. 01.06.2009
page 1/1

PLUS CELLULOSIC SILK MATT VARNISH

Product Description	Short oil alkyd resin and nitrocellulose based, high filling and hiding powered, quick drying and easy to sand primer that holds on to the applied surface very well.
Suggested Uses	Used to form substrate for cellulosic finishing paints for veneer, solid, mdf like surfaces of interior furnitures.
Application Equipments	Compatible with Airless and Airmix spray systems.
Color, Appearance	Yellowish, translucent
Solids Content (%)	31,00 ±2
Density (g/ml)	0,95± 0,20 (20 ° C)
Gloss	60 ° C 40-45 gloss on wood
Viscosity	DINCUP-6 35-40 sc. at 20° C
Mixture Content	Varnish :100 Thinner : 80-100
Dry Time	to touch : 30 min. (at 20°C) to dry hard : 12 hour
Thinner	SOLTECH® Cellulosic Thinner
Storage Conditions	Recommended to be stored in cool and dry places with proper ventilation and no direct sunlight exposure. Should be kept away from sources of fire and heat and necessary fire extinguishing measures should be taken.
Consumption (g/m²)	80-100 (for single coat)
Flas Point	+4 °C
Package Type	12 Kg 3 Kg 0,750 Kg

Technical Consultancy, Application and Process: Verbal, written or practical solutions and recommendations given by our technical service regarding the use of the products are based on the experience and knowledge of our company and does not remove the testing responsibility of the user regarding his/her intended use and is not binding in a way to include the rights of the related third persons. Application, usage and process of the products happen outside of our control opportunity and the entire responsibility belongs to the user. While the responsibility of our company is not fully eliminated, it is limited with the value measure of the products rovided by us and consumed by the user. Needless to say, we guarantee the product continuance of all our products pursuant to our general sales and delivery conditions. New versions of this brochure override the previous ones. Please conform to EC safety forms