

SOLTECH® PLUS CELLULOSIC GLOSSY PAINTS 550 SERIES

Product Description	: Alkyd resin and nitrcellulose based, air-drying, resistant to fading, excellent whiteness and hiding powered gloss paint that forms smooth and regular film.
Suggested Uses	: Used as finishing paint in all wood or metal surfaces, whose surface is prepared with proper primers, of interior furnitures.
Application Equipments	: Compatible with Airless or Airmix spray systems.
Color, Appearance	: Dark brown
Solids Content (%)	: 40,00 ± 2
Density (g/ml)	: 1,00 ± 0,20
Gloss	: 60º 80 – 85 GLOSS (on wood)
Viscosity	: DINCUP6 70 – 75 sec. (at 20 C°)
Mixture Content	: Paint : 100 Thinner : 80 – 100
Dry Time	: To touch : 30 min. Assembly dry : 12 hours
Thinner	: Soltech cellulosic,
Storage Conditions	: Recommended to be stored in cool and dry places with proper ventilation and no direct sunlight exposure. Should be kept away from sources of fire and heat and necessary fire extinguishing measures should be taken.
Consumption (g/m²)	: 80 – 100 (for single coat)
Flash Point	: - 18 C°
Package Type	: 12 kg, 3 kg, 0,850 kg

Technical Consultancy, Application and Process: Verbal, written or practical solutions and recommendations given by our technical service regarding the use of the products are based on the experience and knowledge of our company and does not remove the testing responsibility of the user regarding his/her intended use and is not binding in a way to include the rights of the related third persons. Application, usage and process of the products happen outside of our control opportunity and the entire responsibility belongs to the user. While the responsibility of our company is not fully eliminated, it is limited with the value measure of the products provided by us and consumed by the user. Needless to say, we guarantee the product continuance of all our products pursuant to our general sales and delivery conditions. New versions of this brochure override the previous ones. Please conform to EC safety forms.