

Technical Data Sheet



SOLTECH® GOFRATO PASTE 695 - 0001

Printing date 01.06.2009
page 1/1

Product Description	: Micronized size auxiliary product containing special polypropylene waxes and creating texturized effect.
Suggested Uses	: Can be used to get abrasion resistance, flattening and sanded surface appearance in all solvent based paints and varnishes.
Solids Content(%)	: 66 ± 2
Color, Appearance	: Fuzzy, thixotropic fluid.
Density (g/ml)	: 1,15 ± 0,20 (at 20 C°)
Viscosity	: Cp : 250 S4 (at 25 C°)
Mixture Content	: Varnish - Paint : 100 Gofrato Paste : 5 – 15 (Changes according to desired texture.)
Storage Conditions	: Recommended to be stored in cool and dry places with proper ventilation and no direct sunlight exposure. Should be kept away from sources of fire and heat and necessary fire extinguishing measures should be taken.
Consumption	: Varies according to desired texture.
Flash Point	: +4 C°
Package Type	: 0,750 Kg

Technical Consultancy, Application and Process: Verbal, written or practical solutions and recommendations given by our technical service regarding the use of the products are based on the experience and knowledge of our company and does not remove the testing responsibility of the user regarding his/her intended use and is not binding in a way to include the rights of the related third persons. Application, usage and process of the products happen outside of our control opportunity and the entire responsibility belongs to the user. While the responsibility of our company is not fully eliminated, it is limited with the value measure of the products provided by us and consumed by the user. Needless to say, we guarantee the product continuance of all our products pursuant to our general sales and delivery conditions. New versions of this brochure override the previous ones. Please conform to EC safety forms.