

## Technical Data Sheet



### SOLTECH® ANTI-SILICONE ADDITIVE 695 - 0003

Printing date 01.06.2009  
page 1/1

---

|                            |   |
|----------------------------|---|
| <b>Product Description</b> | : An auxiliary product consisting of special surface regulating agents and aliphatic and aromatic solvent.  |
| <b>Suggested Uses</b>      | : Can be used in all sorts of solvent based paints and varnishes to remove and prevent surface defects like (silicone openings) crater caused by the environment or application equipments.                                 |
| <b>Color, Appearance</b>   | : Colorless, clear liquid.  |
| <b>Density (g/ml)</b>      | : 0,87 ±0,20 ( at 20 C°)  |
| <b>Mixture Content</b>     | : Varnish - Paint : 100 A.S. Additive: 0,50 – 2,00  |
| <b>Storage Conditions</b>  | : Recommended to be stored in cool and and dry places with proper ventilation and no direct sunlight exposure. Should be kept away from sources of fire and heat and necessary fire extinguishing measures should be taken. |
| <b>Flash Point</b>         | : 24 C°   |
| <b>Package Type</b>        | : 0,5 Lt  |

---

**Technical Consultancy, Application and Process:** Verbal, written or practical solutions and recommendations given by our technical service regarding the use of the products are based on the experience and knowledge of our company and does not remove the testing responsibility of the user regarding his/her intended use and is not binding in a way to include the rights of the related third persons. Application, usage and process of the products happen outside of our control opportunity and the entire responsibility belongs to the user. While the responsibility of our company is not fully eliminated, it is limited with the value measure of the products provided by us and consumed by the user. Needless to say, we guarantee the product continuance of all our products pursuant to our general sales and delivery conditions. New versions of this brochure override the previous ones. Please conform to EC safety forms.